

FELLING[®] TRAILERS

EXTREME

(Standard Trailer Specifications)



STANDARD EQUIPMENT - FT-10 LX EXTREME

- 9,980 lb. (4,526 kg) GVWR
- (2) 6,000 lb. axles (4" drop) spring or torsion
- (4) 12" x 2" electric brakes
- (4) ST225/75R15 LRD radial tires
- (4) 6 hole white mod wheels
- Cap. per tire & wheel 2,540 lb. (1,152 kg)
- Adjustable 2⁵/₁₆" ball coupler or 3" lunette eye
- Safety chains (with hooks)
- 7,000 lb. drop-leg jack
- Hitch - 5" channel
- 6" x 4" x 3/8" angle main frame
- 3" Junior I-Beam
- Pressure treated wood deck
- 21" loaded deck height (with 4" drop axles)
- 6 stake pockets, 2 D-rings
- 5' channel type spring assist ramps
- Rubber mounted D.O.T. approved lighting
- Modular wiring harness
- Tool Tray

Model	Width	Length	Approx. Wt.
FT-10 LX	8'6" (81" ID)	16'	2,500#
FT-10 LX	8'6" (81" ID)	18'	2,700#

OPTIONS - AVAILABLE THROUGH FELLING PARTS DEPARTMENT

Spare Wheel & Tire (option, shipped loose)

Bolt on Tire Mount (shipped loose)

LED Lights (shipped loose)

(NO OPTIONS AVAILABLE BESIDES THOSE SPECIFIED ON THIS PAGE.)