



## STANDARD EQUIPMENT - FT-12 EX EXTREME

- 13,800 lb. (6,259 kg) GVWR
- (2) 6,000 lb. axles (4" drop) spring or torsion
- (4) 12" x 2" electric brakes
- (4) ST235/80R16 LRE radial tires
- (4) 8 hole white mod wheels
- Cap. per tire & wheel 3,520 lb. (1,596 kg)
- Adjustable 2<sup>5</sup>/<sub>16</sub>" ball coupler or 3" lunette eye
- Safety chains (with hooks)
- 7,000 lb. drop-leg jack
- Hitch - 5" Channel
- 6" structural channel main frame
- 3" Junior I-Beam
- Pressure treated wood deck
- 22" loaded deck height (with 4" drop axles)
- 8 stake pockets
- 5' channel type spring assist ramps
- Rubber mounted D.O.T. approved lighting
- Modular wiring harness
- Conspicuity tape
- Tool Tray

Model	Width	Length	Approx. Wt.
FT-12 EX	8'6" (82" ID)	16'	2,950#
FT-12 EX	8'6" (82" ID)	18'	3,150#

## OPTIONS - AVAILABLE THROUGH FELLING PARTS DEPARTMENT

Spare Wheel & Tire (option, shipped loose)

Bolt on Tire Mount (shipped loose)

LED Lights (shipped loose)

(NO OPTIONS AVAILABLE BESIDES THOSE SPECIFIED ON THIS PAGE.)