

FELLING® Advanced Design I Series

Felling Trailers, Inc.'s Engineering Team has been working diligently on an advanced design for the I Series model line. This leading-edge design incorporates additional standard features, structural strength, and ease of operator use.



Key Advancements • Hitch Plate • Tailboard • Ramps • 4 Tail Light System LED

STD Specs	FT-10 I	FT-12 I	FT-14 I	FT-16 I	FT-20 I	FT-24 I
Deck Length	16' (other lengths available)	16' (other lengths available)	16' (other lengths available)	18' (other lengths available)	20' (other lengths available)	20' (other lengths available)
Deck Width	102" OD, 82" ID	102" OD, 82" ID	102" OD, 82" ID	102" OD, 83" ID	102" OD, 82" ID	102" OD, 82" ID
Trailer Weight	2,980 lbs.	2,980 lbs.	3,600 lbs.	4,000 lbs.	4,600 lbs.	4,900 lbs.
Deck Height	19" (loaded)	19" (loaded)	21" (loaded)	24" (loaded)	24" (loaded)	24" (loaded)
Deck Type	Pressure Treated	Pressure Treated	White Oak 2" Nom.	White Oak 2" Nom.	White Oak 2" Nom.	White Oak 2" Nom.
Frame	6" x 12# I-beam	6" x 12# I-beam	8" x 15# I-beam	10" x 15# I-beam 3" Angle Iron Lip Up	10" x 17# I-beam 3" Angle Iron Lip Up	10" x 17# I-beam 3" Angle Iron Lip Up
Crossmembers	3" (80K) Jr. I-beam 18" on Center	3" (80K) Jr. I-beam 18" on Center	3" (80K) Jr. I-beam 18" on Center	4" (80K) Jr. I-beam 18" on Center	4" (80K) Jr. I-beam 18" on Center	4" (80K) Jr. I-beam 18" on Center
Axles	7k Dexter EZ Lube	7k Dexter EZ Lube	7k HD Dexter EZ Lube	8k Dexter Oil Bath	10k Dexter Oil Bath	12k Dexter Oil Bath
Suspension	Dexter Spring, 36" Spread	Dexter Spring, 36" Spread	Dexter Spring, 36" Spread	Dexter Spring, 36" Spread	Rubber Torsion, Dexter Torflex, 42" Spread	Rubber Torsion, Dexter Torflex, 42" Spread
Wheels & Tires	ST235/80R 16 E 8 Bolt White Mod	ST235/80R 16 E 8 Bolt White Mod	215/75R 17.5 H 8 Bolt Plate	215/75R 17.5 H 8 Bolt	235/75R 17.5 J 8 Bolt	235/75R 17.5 J 8 Bolt
Tie Downs	(8) D-rings 5/8"	(8) D-rings 5/8"	(8) D-rings 5/8"	(8) D-rings 5/8"	(8) D-rings 1"	(8) D-rings 1"
Ramps	5' x 16" Spring Assist Full Width Ramp Rod	5' x 16" Spring Assist Full Width Ramp Rod	6' x 16" Spring Assist Full Width Ramp Rod	6' x 16" Spring Assist Full Width Ramp Rod	6' x 16" Spring Assist Full Width Ramp Rod	6' x 16" Spring Assist Full Width Ramp Rod
Jack	12K Drop Leg, Side Wind	12K Drop Leg, Side Wind	12K Drop Leg, Side Wind	12K Drop Leg, Side Wind	12K Drop Leg, Side Wind	12K Drop Leg, Side Wind
Lights	4 Tail Light System, LED, Sealed Wiring Harness	4 Tail Light System, LED, Sealed Wiring Harness	4 Tail Light System, LED, Sealed Wiring Harness	4 Tail Light System, LED, Sealed Wiring Harness	4 Tail Light System, LED, Sealed Wiring Harness	4 Tail Light System, LED, Sealed Wiring Harness
GVWR	9,980 lbs.	13,800 lbs.	16,100 lbs.	18,400 lbs.	23,000 lbs.	25,980 lbs.

NOTE: Some models may be shown with optional features.