

Stud Size	Lug Nut Type	Torque Specifications	Wheel Size & Type	Wheel Material
1/2"	Coned	90-120 ft.-lb.	16"	Steel
9/16"	Coned	120-140 ft.-lb.	16"	Steel
5/8"	Coned w/ Wheel Clamp Ring	190-210 ft.-lb.	17.5" Single	Steel
5/8"	Flanged Nuts (Non-Rotating Flange)	275-325 ft.-lb.	17.5" Single	Steel
5/8"	Flanged Nuts (Rotating Flange)	150 -175 ft. lb	17.5" Single	Steel
1/2"	Coned	90-120 ft.-lb.	15"	Steel
5/8"	Coned w/ Wheel Clamp Ring	190-210 ft.-lb.	16" Dual	Steel
5/8"	Flanged Nuts (Non-Rotating Flange)	275-325 ft.-lb.	16" Dual	Steel
5/8"	Flanged Nuts (Rotating Flange)	150 -175 ft. lb	16" Dual	Steel
M22-1.5	SWIVEL FLANGE	450-500 ft.-lb.	17.5 Dual 8on275mm	Steel
M22-1.5	SWIVEL FLANGE	450-500 ft.-lb.	17.5 Dual 8on275mm	Aluminum
5/8"	2-piece Lug Nut	140-160 ft.-lb.	17.5" Single	Aluminum