

ST- Fixed Single Booster

X-Force Acc Series

GVWR LBS:

24,800

GAWR LBS:

22,500

WEIGHT LBS:

4,800

CAPACITY LBS:

20,000

- Hydraulic Single Axle Spreader Bar
- 16' upward, 4" downward travel (appx)
- 25K fixed axle
- 20,000 lbs Capacity

- Nitrogen Accumulator
- 5.5 HP Honda Gas Motor
- Air Ride suspension
- Raises appx 12" off the ground



Standard & Other Options	Description	Std. Option	Std. Qty.	Unit	List Price	Add'l Each
Load Capacity	Up to 20,000 lbs Capacity	X	1.00	Std	0.00	0.00
Overall Length	Overall Length in Feet	X	15.00	Feet	0.00	0.00
Width	102" OD	X	102.00	Inches	0.00	0.00
Tie Downs	D-rings, On Top of Booster	X	1.00	Std	0.00	0.00
Brakes	Air, Non- ABS	X	1.00	Std	0.00	0.00
Axles	25K Oil Bath	X	1.00	Std	0.00	0.00
Suspension	Axle, Air Ride with Dump Valve and Pressure Gauge	X	1.00	Std	0.00	0.00
Suspension	Booster Flexibility allows Axle travel of appx 15" Up & 4" Down	X	1.00	Std	0.00	0.00
Tires & Wheels	275/70R 22.5 H, 10 Bolt [22.5 x 8.25] Hub Pilot	X	4.00	Each	0.00	0.00
Jack	12K Drop Leg	X	1.00	Std	0.00	0.00
Plug	7 Pole Semi	X	1.00	Std	0.00	0.00
Lights	Amber LED Strobe Lights, Switched and Mounted in Tailboard, re places 2 center tail lights	X	1.00	Std	0.00	0.00
Lights	Sealed Wiring Harness	X	1.00	Std	0.00	0.00
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std	0.00	0.00
Stripe Color	White	X	1.00	Std	0.00	0.00
Standard	5.5 HP Honda Gas Motor	X	1.00	Std	0.00	0.00
Standard	Nitrogen Accumulator Tank	X	1.00	Std	0.00	0.00
GVWR	24,800 lbs	X	1.00	Std	0.00	0.00