

<b>Product ID</b>	FT-14-2 R Self Loading Turret Trailer	<b>OVL Length:.</b>	15	<b>Appx Wgt +/-:</b>	3,000
-------------------	---------------------------------------	---------------------	----	----------------------	-------



Model Shown With Optional Features

Item Type	Description	Add Qty	Unit	Total Qty
<b>Base Model</b>	<b>FT-14-2R Self Loading Turret Trailer</b>	0.00	Each	1.00
<b>Frame Type</b>	<b>Turret Assembly - 86" dia x 60" wide x 5,000 lb Reel Capacity. 2 7/8" dia. Reel Bar. Complete 360 degree Rotation. Lockable Positons Every 15 degrees. HD Slew Bearing - 105,000 lbs Axial and 40,000 lbs Moment Load Capacity. Bronze Reel Bushing</b>	0.00	Opt	1.00
<b>Frame Type</b>	<b>Turret Mounted On Self-Loading Frame Assembly, Twin 4" Hydraulic Cylinders. Hinges at and Picks Up From Rear of Trailer</b>	0.00	Opt	1.00
Deck Length	Main Deck Length	0.00	Feet	10.00
<b>Width</b>	<b>102"</b>	0.00	Opt	1.00
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	0.00	Std	1.00
<b>Brakes, Acc</b>	<b>** Custom ** - Dexter Tow Assist - ABS &amp; Sway Mitigation System</b>	0.00	Opt	1.00
Axles	7K Dexter, Drop	0.00	Std	2.00
Suspension	Dexter Spring	0.00	Std	1.00
<b>Tires &amp; Wheels</b>	<b>ST235/80R 16 E, 8 Bolt [16 x 6] *Black* Mod</b>	0.00	Each	4.00
<b>Option</b>	<b>Steel Treadplate Fenders with Mudflaps</b>	0.00	Opt	1.00
Hitch Length	Center of Coupler to Headboard, Appx	0.00	Feet	5.00
Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	0.00	Std	1.00
Jack	12K Drop Leg ** Side Wind **	0.00	Std	1.00
Jack	2 Rear Stabilizer Legs	0.00	Std	2.00
<b>Option</b>	<b>Hydraulic Rear Stabilizer Jacks in lieu of The Standard Drop Down Jacks.</b>	0.00	Opt	2.00
Plug	7 Pole RV	0.00	Std	1.00
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	0.00	Std	1.00
<b>Trailer Color</b>	<b>Sublime Green *45th Anniversary Color* # CCA953995(Black Felling Decal)</b>	0.00	Opt	1.00
<b>Stripe Color</b>	<b>Black</b>	0.00	Opt	1.00
Standard	3/8" Safety Chains, Grade 70	0.00	Std	1.00
Standard	Document Holder	0.00	Std	1.00
<b>Option</b>	<b>HYD Retriever/Take up, Direct Connection to Reel Bar. 2.100 lbs of Line Pull. Can Also be Used as a Hydraulic Tensioner - 500 lbs Minimum Continuous Tension Up To 86" Diameter Wrap.</b>	0.00	Opt	1.00
<b>Option</b>	<b>13 HP Hyd. Power unit (Honda Engine w/electric start) Includes Enclosure, 8 gpm @ 2,250 psi, 25 Gallon Hydraulic Reservoir</b>	0.00	Opt	1.00
<b>Option</b>	<b>Hydraulic Rotary Manifold. Eliminates Excess Hydraulic Lines Needed for Rotation of the Turret Assemblies.</b>	0.00	Opt	1.00
<b>Option</b>	<b>16" Tensioning Brake</b>	0.00	Opt	1.00
GVWR	16,100 lbs	0.00	Std	1.00