

<b>Product ID</b>	FT-16 IT-I	<b>Serial No.</b>	5FTCE282XL1005369	<b>OV Length:.</b>	28	<b>Appx Wgt +/-:</b>	5,200
-------------------	------------	-------------------	-------------------	--------------------	----	----------------------	-------

REF. No. 118756-NTU



Item Type	Description	Add Qty	Unit	Total Qty
Base Model	FT-16 IT-I Drop Deck Tilt [E]	0.00	Each	1.00
<b>Stationary Deck</b>	<b>Stationary Deck</b>	<b>1.00</b>	<b>Feet</b>	<b>5.00</b>
<b>Deck Length</b>	<b>Tilt Deck Length (Includes 2' Steel Punch Plate Approach)</b>	<b>2.00</b>	<b>Feet</b>	<b>18.00</b>
<b>Deck Type</b>	<b>Blackwood, Rubber Infused Lumber</b>	<b>0.00</b>	<b>Feet</b>	<b>23.00</b>
Appx Deck Height	22.5" Loaded, 24.5" Unloaded	0.00	Inches	1.00
Width	102" OD, 81" ID	0.00	Inches	1.00
Tie Downs	D-Rings, 5/8 Straight	0.00	Std	10.00
<b>Tie Downs</b>	<b>Rub Rail and Stake Pockets</b>	<b>0.00</b>	<b>Feet</b>	<b>23.00</b>
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	0.00	Std	1.00
Axles	8K Dexter Oil Bath Drop	0.00	Std	2.00
<b>Suspension</b>	<b>Rubber Torsion, Dexter TorFlex, 42" Spread</b>	<b>0.00</b>	<b>Opt</b>	<b>1.00</b>
<b>Tires &amp; Wheels</b>	<b>215/75R 17.5 H, 8 Bolt [17.5 x 6.75] *Black* Plate Wheel</b>	<b>0.00</b>	<b>Each</b>	<b>4.00</b>
Hitch Length	Center of Coupler to Headboard, Appx - Adj Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)	0.00	Feet	5.00
Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt),	0.00	Std	1.00
<b>Jack</b>	<b>Dual 12K Drop Leg</b>	<b>0.00</b>	<b>Pair</b>	<b>1.00</b>
Plug	7 Pole RV	0.00	Std	1.00
Lights	LED, 4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)	0.00	Std	1.00
<b>Trailer Color</b>	<b>Sublime Green *45th Anniversary Color* # CCA953995(Black Felling Decal)</b>	<b>0.00</b>	<b>Opt</b>	<b>1.00</b>
Standard	3/8" Safety Chains, Grade 70	0.00	Std	1.00
Standard	Document Holder	0.00	Std	1.00
<b>Spare Tire</b>	<b>215/75R 17.5 H, 8 Bolt [17.5 x 6.75] *Black* Plate Wheel</b>	<b>0.00</b>	<b>Each</b>	<b>1.00</b>
<b>Spare Tire, Acc</b>	<b>Spare Tire Mount - Bolted to Removable Rack (Front)</b>	<b>0.00</b>	<b>Each</b>	<b>1.00</b>
<b>Option</b>	<b>Dual Cylinders with Lock Valve</b>	<b>0.00</b>	<b>Opt</b>	<b>1.00</b>
<b>Option</b>	<b>Pallet Fork Holders Mounted 36" O.D. of Tubes with Fork Securement Chains</b>	<b>0.00</b>	<b>Pair</b>	<b>1.00</b>
<b>Option</b>	<b>Tool Box, Medium 57" x 16" x 11", Bolt on with Lockable Cover, 4.6 Cu Ft</b>	<b>0.00</b>	<b>Each</b>	<b>1.00</b>
<b>Option</b>	<b>Removable Attachment Rack: 54" Deck height x 5' length x Full width of deck - 81" ID Between Uprights, Upper Deck Angle Lip Up on Front and Each Side, Rub &amp; Stake each side, Deck with Blackwood ** 2,500 lb Capacity **</b>	<b>0.00</b>	<b>Opt</b>	<b>1.00</b>
<b>Option</b>	<b>Rack Cont.: 3 Bolt On Round Tubes For Shovels/Brooms on Drivers Side, side bracing positioned high enough to side load (appx 36" ID height), Rack Uprights to fit into std size stake pockets, Rack Painted Black</b>	<b>0.00</b>	<b>Opt</b>	<b>1.00</b>
GVWR	18,400 lbs	0.00	Std	1.00