



ISO 9001 Quality Management System | WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974

**Product Sheet**

Felling Trailers, Inc. 2021

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

<b>FT-14 PCD</b>	<b>Utility Pole Cargo Dump</b>
<b>GVWR LBS: 16,100</b>	<b>GAWR LBS: 14,000</b>
	<b>WEIGHT LBS: 6,000</b>
	<b>CAPACITYLBS: 10,100</b>

Feature Name	Standard Features	Qty	Unit Price	UOM
<b>Model</b>	<b>FT-14 PCD</b>	1	\$ -	
<b>Overall Length</b>	24' Retracted / 40' Extended / 12' Bed	24	\$ -	Feet
<b>Cargo Deck</b>	Hydraulic Dump Bed	12	\$ -	Feet
<b>Rear Gate</b>	Drop Down Rear Tailgate	1	\$ -	Std
<b>Width</b>	96" OD x 72" Inside Bed	1	\$ -	Std
<b>Appx Deck Height</b>	30" Unloaded (Appx)	1	\$ -	Inches
<b>Tie Downs</b>	D-Rings, 5/8" Straight, Mounted in Box Corners	4	\$ -	Std
<b>Brakes</b>	Electric, FSA (Fwd Self Adj) On All Axles	1	\$ -	Std
<b>Axles</b>	7K, Straight	2	\$ -	Std
<b>Deck Type</b>	3/16" Smooth Steel	1	\$ -	Std
<b>Hitch Type</b>	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	1	\$ -	Std
<b>Option</b>	14" Tall X 14" Deep X Full Width Steel Toolbox Contoured to A-Frame With Side opening Doors	1	\$ -	Std
<b>Suspension</b>	Spring **Underslung**	1	\$ -	Std
<b>Tires &amp; Wheels</b>	ST235/80R 16 E, 8 Bolt [16 x 6] Mod	4	\$ -	Std
<b>Jack</b>	12K w/ Spring Loaded Drop Leg, Side Wind	1	\$ -	Std
<b>Plug</b>	7 Pole RV	1	\$ -	Std
<b>Lights</b>		1	\$ -	Std
<b>Lights</b>		1	\$ -	Std
<b>Stripe Color</b>	White	1	\$ -	Opt

<b>Standard</b>	Center and Rear Bolsters, 96" Wide Bolsters with 21" Sliding Lever Lock Stanchions with Winch Binder and 30" x 4" Strap (Located Curb Side)	1	\$	-	Std
<b>Standard</b>	Document Holder	1	\$	-	Std
<b>Standard</b>	Tread Plate Fenders	1	\$	-	Std
<b>Standard</b>	3/8" Safety Chains, Grade 70	1	\$	-	Std
<b>Standard</b>	Front Bolster, Adjustable & Removable, 45" Wide Bolster Mounted on Extended Portion of Tongue, Winch Binder & 4"x30' Strap(Located Curb Side)	1	\$	-	Std
<b>Standard</b>	36" Winch Bar	1	\$	-	Std
<b>Standard</b>	Heavy Duty Battery, Pump and Remote with 15ft Cord	1	\$	-	Std
<b>Standard</b>	Dual Hydraulic Cylinder	1	\$	-	Each
<b>GVWR</b>	16,000 lbs	1	\$	-	Std