

FT-45-2 LP Paver

FELLING TRAILERS, INC. 1525 Main Street South, Sauk Centre, MN 56378 Phone: 800-245-2809 - www.felling.com

certified

2600-F





		Reference No: 257444NTU WOA 2024 OV	Length: 41	Appx Wgt +/-:	13,000 lbs
Item Type	Options	Description	Add Qty	Unit	Total Qty
Base Trailer		FT-45-2 LP Paver		Each	0
Deck Length		Add Main Deck Length (Pierced Frame)		Feet	26
Frame Type		Engineered Fabricated Hi-Tensile Grade 80 Main Frame Beams		Std	1
		with Grade 80 Jr-I Cross-Members			
Beavertail		Wood Inlaid Beavertail		Feet	6
Beavertail, Acc		Double Incline		Opt	1
Deck Type	1	Apitong, 1 3/8"		Feet	43
Ramps; Rear		45" Wide x 11' (7.5'+3.5') Bi-Fold, Air Operated, Wood Inlaid		Pair	1
		(Includes 3 large air tanks & Bolt on Ramp Legs)			
Appx Deck heigh	ıt	33" Loaded, 35" Unloaded		Inches	1
Width		102" OD		Feet	32
Tie Downs	1	D-Rings, 1" ** Straight ** (One Set Centered on BVT)	4	Each	22
Brakes		Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)		Each	1
Axles		25K Oil Bath		Std	2
Suspension		25,000 lb Heavy Duty 3 Leaf Springs		Std	1
Suspension		49" Spread (Spring), 9700 Hutch		Std	1
Tires & Wheels		235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot		Std	8
Tires & Wheels,	Acc 🖌	Aluminum 17.5" 8 Bolt Hub Pilot (Polished) (outers only)		Each	4
Hitch Length		Center of Coupler to Headboard, Appx		Feet	6.3
Hitch Type		3" Adjustable Lunette Eye/Pintle, [C] 66,000 lb Plate Mount (3/4" Bolt)		Std	1
Jack		140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)		Pair	1
Jack	1	**Custom**-		Opt	1
		On-Lift Air Powered Landing Gear Automation (Patriot Lift System			
Plug		7 Pole Semi		Std	1
Lights	1	Amber LED Strobe Lights, Switched and Mounted, replaces 2		Opt	1
		center tail lights (Battery Powered)			
Lights		LED Lights (Peterson), Sealed Wiring Harness (Sealco)		Std	1
Lights	1	Additional Clearance Lights Spaced Evenly On Side Of Trailer - LED (Per Pair)		Pair	2
Trailer Color	1	Bold Yellow # CCA945381 (Black Felling Decal)		Opt	1
Stripe Color	1	Chrome		Opt	1
Standard		1/2" Safety Chains, Grade 70		Std	1
Standard		Toolbox, Extended as far forward as possible (with lockable		Std	1
		latch) in a-frame area of hitch			
Standard		Document Holder		Opt	1
Standard		2 Steps,1 on the Standard Hitch and 1 in front of Axles on Roadside		Std	2
GVWR		53,900 lbs		Std	1